

Proiect:		Type:
	0.1.1	
Drawn by:	Catalogue #:	Date:

# Series spec sheet

# **SRC**

# RECESSED REMOTE

MR16 Recessed Ceiling Adjustable Gimbal 6 V, 12 V, & 24 V lamps

The SRC series of commercial recessed MR16 remotes has been designed to blend seamlessly into modern decors. The backbox can be mounted in a variety of ways above suspended or drywall ceilings, leaving only the lamp and compact trim plate visible. Trimplates snap into the housing and come in a variety of colors and finishes. The SRC is available in 6 V, 12 V, and 24 V models, all utilizing low glare, MR16 LED lamps.

#### FEATURES AND SPECIFICATIONS

#### Mechanical

- Steel housing/backbox and trim plate
- Backbox recesses completely above ceiling
- Backbox c/w plaster ring and adjustable T-bar or nail-in hanger bars
- Adjustable gimbal mounted lamp
- White trim paint finish is standard, other colors and finishes are optional
- MR16 lamp designed with low glare reflector and available in 6 VDC, 12 VDC or 24 VDC

#### Compliances

- CSA Certified to C22.2 #141-15
- Meets requirements of ICES-005

#### **OVERVIEW**

Light source	LED
Input voltage (VDC)	6, 12, 24









**((•))** 

**ICES** 



For complete warranty details, please see our terms and conditions on our website.




### **ORDERING GUIDE**

SRC	1 -									
Series	Number of heads	Volts (VDC operational)		Watts (W)		Туре		Color		Option
SRC - Construction	1 - Single head	06-24V -	6 to 24	4 -	4	LR -	LED	WH -	White (standard)	<b>SQ</b> - Square trim <sup>1</sup>
model				5 -	5	LA -	LED	BK -	Black	
		12-24V -	12 to 24	6 -	6	LA -	LED	SC -	Satin chrome	
				7 -	7			SP -	Custom color (specify)	

<sup>&</sup>lt;sup>1</sup> For Black square trim, contact your rep for availability

## **DIMENSIONS**



## **SPACING GUIDE**

Mounting	Spacing center to center (ft)					
height	4WLR	5WLA	6WLA	7WLA		
8 ft	76	81	94	108		
10 ft	79	79	93	106		
15 ft	66	62	82	96		
20 ft	53	49	73	87		

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

