

# Choose the right LED Downlight

All of our LED downlights are available in quick ship and certified Energy Star.



		LPDL - Low profile downlight		Swivel	Gimbal		Retro	Vivio	Presto	CDU	CDU Gen 2
		Choice	Stanpro	Choice	Gimbal 7W	Gimbal HO					
<b>Main selling features</b>		Ultra slim recessed downlight, less than 1" thick, perfect for shallow or constraint ceiling spaces		Directional downlight which can highlight specific zones with 360° rotation and up to 90° tilt	Small aperture and highly versatile design with directional light output	Outstanding performance, small aperture and recessed design with directional light output	Retrofit solution with E26 screw-in adaptor for existing recessed cans, easy installation	Dual installation offering both retrofit option or mounted directly into a 4" junction box	Quick installation with LED driver mounted directly on top of the light engine	All-in-one commercial downlight with integrated 3 CCT and 4 power selectable	All-in-one commercial downlight with integrated 3 CCT and 3 power selectable
<b>Size(s) (in)</b>		4, 6	3, 4, 6	4	3, 4	3.5	4, 5-6	4	4, 6	4, 6, 8	4, 6, 8
<b>Shape</b>											
<b>Watts (W)</b>		11, 14	7, 9, 12	8, 9	7	12	10, 12, 15	8	7, 9	6/9/12/15 10/15/20/25 20/25/30/35	7/9/12 12/16/20 15/20/25
<b>Lumen output (lm)</b>		750, 1 100	Round: 500, 600, 820 Square: 450, 550, 780	Single CCT: 750 CCT Selectable: Up to 650	Warm Dim: 470 Single CCT: Up to 620	Warm Dim: 660 Single CCT: Up to 950 CCT Selectable: 850	Single CCT: 650, 850 CCT Selectable: 700, 1 100	650	550, 700	500/750/1 000/1 200 900/1 350/1 850/2 000 1 850/2 200/2 700/3 000	595/765/1 000 1 080/1 440/2 000 1 800/2 200/2 900
<b>Volts (VAC)</b>		120	120	120	120	120	120	120	120	120-347	120-347
<b>Color Temp. (K)</b>	Single	3 000	2 700, 3 000, 4 000, 5 000	3 000	3 000, 4 000	3 000, 4 000	2 700, 3 000, 4 000		2 700, 3 000, 4 000		
	Warm Dim		3 000-2 200		3 000-2 200	3 000-2 200					
	Selectable	3 CCT: 2 700/3 000/4 000	5 CCT: 2 700/3 000/3 500/4 000/5 000	3 CCT: 2 700/3 000/4 000		5 CCT: 2 700/3 000/3 500/4 000/5 000	5 CCT: 2 700/3 000/3 500/4 000/5 000		5 CCT: 2 700/3 000/3 500/4 000/5 000	3 CCT: 3 000/3 500/4 000	3 CCT: 3 000/3 500/4 000
<b>Color finish</b>											
<b>CRI</b>		80+	80+	90+	80+, 90+	90+	90+	80+	80+	90+	80+
<b>Beam angle</b>											
<b>Location</b>											
<b>Dimmable</b>		ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC		0-10 V
<b>Cable rated</b>		FT4	FT4, FT6	FT4	FT4	FT6					
<b>Warranty (year)</b>		5	7	5	5	5	5	3	5	5	5
<b>IC rated</b>		✓	✓	✓	✓	✓			✓		✓
<b>Airtight</b>		✓	✓	✓	✓	✓	✓	✓	✓		
<b>Other details</b>		Available in a bulk pack of 10 units <sup>1</sup>			Interchangeable trims, increase flexibility and reduce inventory level Available in all-in-one kit either 3" or 4" in white	Available in individual bulk pack of 10 drivers and 10 LED modules for 2-phases job site deliveries <sup>2</sup>		Black magnetic trim sold separately <sup>3</sup>	Optional trim accessory finish White, Bronze, Silver and Black <sup>3</sup>		

<sup>1</sup> Only available in 4" 30K white    <sup>2</sup> Only available in 3.5" 30K white    <sup>3</sup> Sold separately