



## WPS GEN 4 Classic Wall Pack

Selectable color temperature (3 000 K / 4 000 K / 5 000 K), Power selectable, Integrated photocell and Multi-Voltage (120-347V)<sup>1</sup>



## Features

- Power selectable<sup>1</sup>
- 4 000 K, 5 000 K and 3 CCT select (3 000 K / 4 000 K / 5 000 K)<sup>1</sup>
- Integrated Photocell that can be easily disabled<sup>1</sup>
- 0-10 V dimmable
- Prismatic tempered glass lens
- 120-277 V, 120-347 V
- Ambient temperature: -40°C to +50°C
- Options: Occupancy sensor, 10 kV surge protection, Paintable
- Accessories: Glareshield, Wireguard, Back plate






### Selectable color temperature and ON/OFF integrated photocell<sup>1</sup>



### Power selectable<sup>1</sup>

	Order code	
Power Selection	68314	68315
1	25 W	60 W
2	30 W	80 W
3	40 W	100 W



Order code	Model number	Watts (W)	Volts (V)	Color temp. (K)	Lumen output (lm)	Efficiency (lm/W)	Photo-cell <sup>2</sup>	CRI	Life L70 (hrs)	Tested hours LM-80 (hrs)	Calculated TM21 (hrs)	Finish	Dimming	LED current (mA)	Power factor	THD (%)	Case qty (master)
<b>Power Select, CCT Select and Integrated Photocell<sup>2</sup></b>																	
68314	WPS-PS40-Q-3C	25/30/40	120-347	3CCT (30/40/50)	3 625 - 5 800	140-150	Yes	>80	54 000	9 000	173 600	Bronze	Yes	850	≥0.9	≤20	1
68315	WPS-PS100-Q-3C	60/80/100	120-347	3CCT (30/40/50)	8 520 - 14 500	140-152	Yes	>80	54 000	9 000	173 600	Bronze	Yes	2 100	≥0.9	≤20	1
<b>Single Power, Single CCT and Integrated Photocell<sup>2</sup></b>																	
68524	WPS-NS30-W/40K	29	120-277	4 000	4 200	150	Yes	>80	54 000	9 000	173 600	Bronze	Yes	230	≥0.9	≤20	1
68525	WPS-NS30-W/50K	29	120-277	5 000	4 300	148	Yes	>80	54 000	9 000	173 600	Bronze	Yes	230	≥0.9	≤20	1
<b>Single Power and Single CCT</b>																	
68490	WPS-NS40-W/40K	40	120-277	4 000	6 004	142	No	>80	54 000	9 000	173 600	Bronze	Yes	354	≥0.9	≤20	1
68491	WPS-NS40-W/50K	40	120-277	5 000	6 034	144	No	>80	54 000	9 000	173 600	Bronze	Yes	354	≥0.9	≤20	1
68492	WPS-NS60-W/40K	60	120-277	4 000	8 458	146	No	>80	54 000	9 000	173 600	Bronze	Yes	486	≥0.9	≤20	1
68493	WPS-NS60-W/50K	60	120-277	5 000	8 611	147	No	>80	54 000	9 000	173 600	Bronze	Yes	486	≥0.9	≤20	1
68497	WPS-NS80-W/40K	80	120-277	4 000	11 242	146	No	>80	54 000	9 000	173 600	Bronze	Yes	645	≥0.9	≤20	1
68498	WPS-NS80-W/50K	80	120-277	5 000	11 446	148	No	>80	54 000	9 000	173 600	Bronze	Yes	645	≥0.9	≤20	1
<b>Single Power, CCT Select and Integrated Photocell<sup>2</sup></b>																	
68316	WPS-NS120-Q-3C	120	120-347	3CCT (30/40/50)	16 943 - 17 885	140-152	Yes	>80	54 000	9 000	173 600	Bronze	Yes	2 600	≥0.9	≤20	1

<sup>1</sup> Integrated photocell, CCT and Power selectable on some configurations. Consult Quick ship and technical specification table for more details.

<sup>2</sup> Integrated ON/OFF photocell that can be easily disabled.

Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at [www.designlights.org/search](http://www.designlights.org/search).