

EMERGENCY LIGHTING

Options

For the list of options available to a specific series, please consult its catalogue page

Option	Description
A	Ammeter
ACTB	AC Terminal Block
AT	Automatic test Self-diagnostic
AUD	Audible Alarm
AUE	Audible Emergency
BO	Black Out Option (for special wording only)
WO	White Out Option (for special wording only)
BD	Battery Disconnect
CCWH	White end caps & canopy kit (RMEA only)
DCTB	DC Terminal Block
FD6	6 Circuit Fused Internal Distribution
HTR	Internal thermostatically controlled battery heater (specify voltage)
IRT	Infrared Remote Test (120/347 VAC)
K5	1/2" Knockout for pendant mount
LCP	Less Canopy

Option	Description
LGD	Die Cast Lens Guard
LC	120 VAC line cord
LD	Lamp Disconnect (internal)
LT	Remote Laser Test (contact factory)
PGD	Lexan Guard (separate order)
VS	Vandal resistant wraparound shield (RML only)
MS	Mounting Shelf (separate order)
OBM	Octagon Box Mount (line cord delete)
RFS	Radio Frequency Suppression (specify AC voltage)
SMH	Side Mounted Heads
OP	Special Wording
TD	Time Delay (specify AC voltage)
TLP	Twist Lock Plug (specify AC voltage)
TP	Tamper Proof Screws
V	Voltmeter
WGD	Wireguard (separate order)

Glossary

Term	Description
IB	Self-powered for 90 minutes
IB1	Self-powered for 120 minutes
NDC	No DC backup voltage
UDC	Universal DC backup voltage from 6 to 24 V DC